


## BARRICADES

NOTES 1, 2




## TUBULAR MARKERS

DAYLIGHT HOURS ONLY



## CONES

DAYLIGHT HOURS ONLY




ONE-PIECE RECTANGULAR  
W/REFLECTIVE BANDS

TWO-PIECE ROUND  
W/REFLECTIVE BANDS

PLASTIC DRUMS

SEE NOTE 4




## VERTICAL PANELS


SEE NOTE 1

## ADVANCE WARNING ARROW PANELS

SEE NOTE 3



STATE MAINTENANCE AND STATE FUNDED PROJECTS ONLY



NOTES:

1. A MINIMUM OF 270 SQUARE INCHES OF RETROREFLECTIVE MATERIAL PLACED A MINIMUM OF 12 INCHES ABOVE THE ROADWAY SURFACE IS REQUIRED ON BARRICADES AND VERTICAL PANELS WHEN USED ON THE INTERSTATE OR ROADWAYS WITH A POSTED SPEED OF GREATER THAN 45 MPH. PLACE BARRICADES AND VERTICAL PANELS IN SUCH A MANNER THAT THEY ARE VISIBLE TO APPROACHING TRAFFIC.
2. USE SANDBAGS WITH SAND OR OTHER COMPARABLE SOFT MATERIAL AS BALLAST. DO NOT PLACE BALLAST HIGHER THAN 12 INCHES ABOVE THE ROADWAY AND DO NOT COVER ANY REFLECTIVE AREA OF RAILS OR SIGNS.
3. PLACE THE BOTTOM EDGE OF THE ADVANCE WARNING ARROW PANELS A MINIMUM OF 7 FEET ABOVE THE ROADWAY SURFACE.
4. USE PLASTIC DRUMS AS LANE CLOSURE TAPER DEVICES FOR SPEEDS 50 MPH AND GREATER.

[illegible]